





## Difference between HQ and H

Difference	MT6070HQ	MT6070H
Back image		
Dimension	210*146*36mm	212*148*40mm
Cutout size (Universal old shell)	192*138mm	194*138mm
Light hole	No	2
HMI download port	TYPE-C cable	Type B male cable
SD card slot	Default (Optional SD card and USB coexist)	Optional (Optional SD card conflicts with USB)
DB9 port	1	2
RS232	Pin 2, 3, 5 of COM	Pin 2, 3, 5 of COM1
RS485	A1, B1	Pins 1, 6 of COM1/COM2

Difference	EX3G-70HQ	EX3G-70H
Back image		
Dimension	210*146*36mm	212*148*40mm
Cutout size (Universal old shell)	192*138mm	194*138mm
Digital I/O	Max 24 DI 20 DO (MR16)	Maximum 24 in 20 out (MR18)
SD card slot	Default (Optional SD card and USB coexist)	Optional (Optional SD card conflicts with USB)
DB9 port	1	2
PLC-RS232	Pin 2, 3, 5 of COM	Pin 2, 3, 5 of COM1
PLC-RS485	Default A, B	Optional on: pins 1, 6 of COM1
HMI-RS232	Default on: pin 4, 7, 5 of COM	Optional on: pin 2, 3, 5 of COM2
HMI-RS485	Optional A1, B1	Optional on: pins 1, 6 of COM2